

In the claims:

Please amend the claims as follows:

-
1. (Currently Amended) A heat radiating device comprising:
a heat radiating substrate containing Al as a major component; and
a metal film containing Cu, Ag, Sn, Ni, or Au disposed on the heat radiating substrate;
and
an oxide film formed on a front and back surface of the heat radiating substrate.
2. (Previously Amended) A heat radiating device according to claim 1, wherein the metal film consists of a plating film.
3. (Previously Amended) A heat radiating device according to claim 1, wherein the metal film is configured to contact a metal body provided on a back surface of a semiconductor device.
4. (Previously Amended) A heat radiating device according to claim 1, wherein a surface of the heat radiating substrate opposite to the surface over which the metal film is disposed is coupled to an external device.
5. (Currently Amended) A semiconductor module comprising:
a semiconductor device including a semiconductor element, pads coupled electrically to bonding electrodes of the semiconductor element, and an island disposed on a back surface of the semiconductor element, said semiconductor device integrally sealed with resin except where the island and the pads are disposed; and
a heat radiating substrate containing Al as a major component; and
a first metal film containing Cu, Ag, Sn, Ni, or Au and disposed on the heat radiating substrate,
wherein the first metal film and the island are coupled by brazing solder, conductive paste, or adhering material having thermal conductivity; and

an oxide film formed on a front and back surface of the heat radiating substrate.

6. (Previously Amended) A semiconductor module according to claim 5, wherein a second metal film containing Cu as a major component is disposed between the first metal film and the island.

7. (Original) A semiconductor module according to claim 6, wherein the island and the metal plate are formed integrally by the etching process.

8. (Original) A semiconductor module according to claim 5, wherein a back surface of the semiconductor element is adhered to the metal plate.

9. (Original) A semiconductor module according to claim 5, wherein back surfaces of the pads and a back surface of the island are arranged substantially on a same planar surface.

10. (Original) A semiconductor module according to claim 8, wherein back surfaces of the pads and a back surface of the semiconductor element are arranged substantially on a same planar surface.

11. (Previously Amended) A semiconductor module according to claim 9 or claim 10, wherein a back surface of the insulating resin projects beyond back surfaces of the pads.

12. (Previously Amended) A semiconductor module according to claim 11, wherein side surfaces of the pads and the back surface of the insulating resin extending from the side surfaces of the pads draw a same curved surface.

13. (Previously Amended) A semiconductor module according to claim 12, further comprising: a flexible sheet having conductive patterns coupled electrically to the semiconductor device, said sheet provided between the semiconductor device and the radiation substrate; and

an opening provided in the flexible sheet to correspond to the island.

14. (Currently Amended) A semiconductor module comprising:

a semiconductor device including a semiconductor element, pads coupled electrically to bonding electrodes of the semiconductor element, and a radiating electrode disposed on a back surface of the semiconductor element, said semiconductor element integrally sealed with resin except where the radiating electrode and the pads are disposed;

a heat radiating substrate containing Al as a major component; ~~and~~

a first metal film containing Cu, Ag, Sn, Ni, or Au disposed on the heat radiating substrate,

wherein the first metal film and the radiating electrode are coupled by brazing solder, conductive paste, or adhering material having thermal conductivity; and
an oxide film formed on a front and back surface of the heat radiating substrate.

15. (Previously Amended) A semiconductor module according to claim 14, further comprising:

a second metal film containing Cu as a major component and disposed between the first metal film and the radiating electrode.

16. (Previously Amended) A semiconductor module according to claim 14, wherein the radiating electrode and the metal plate are formed integrally by etching.

17. (Previously Amended) A semiconductor module according to claim 14, wherein back surfaces of the pads and the back surface of the radiation electrode are arranged substantially on a same planar surface.

18. (Previously Amended) A semiconductor module according to claim 17, wherein a back surface of the insulating resin projects beyond the back surfaces of the pads.

19. (Previously Amended) A semiconductor module according to claim 18, wherein side surfaces of the pads and the back surface of the insulating resin extending from the side surfaces of the pads draw a same curved surface.

20. (Previously Amended) A semiconductor module according to claim 19, further comprising:

a flexible sheet having conductive patterns coupled electrically to the semiconductor device, said flexible sheet provided between the semiconductor device and the heat radiating substrate; and

an opening provided in the flexible sheet to correspond to the radiating electrode.

21. (Currently Amended) A semiconductor module comprising:

a semiconductor device including a semiconductor element, leads coupled electrically to bonding electrodes of the semiconductor element, and an island whose back surface is disposed on a same surface level as a back surface of the leads; and

a heat radiating substrate containing Al as a major component; ~~and~~

a first metal film containing Cu, Ag, Sn, Ni, or Au disposed on the heat radiating substrate,

wherein the first metal film and the island are coupled by brazing solder, conductive paste, or adhering material having thermal conductivity; and

an oxide film formed on a front and back surface of the heat radiating substrate.

22. (Previously Amended) A semiconductor module according to claim 21, further comprising:

a second metal film containing Cu as a major component, said second metal film disposed between the first metal film and the island.

23. (Previously Amended) A semiconductor module according to claim 22, further comprising:

a flexible sheet having conductive patterns coupled electrically to the semiconductor device, said flexible sheet provided between the semiconductor device and the heat radiating substrate, and

an opening provided in the flexible sheet to correspond to the island.

24. (Original) A semiconductor module according to claim 13, claim 20 or claim 23, wherein the semiconductor device is a read/write amplifier IC for a hard disk.

25. (Previously Amended) A semiconductor module according to claim 13, claim 20 or claim 23, wherein the semiconductor device couples electrically to an external device through the heat radiating substrate.

32. (Currently Amended) A heat radiating device comprising:
a heat radiating substrate containing Al as a major component; ~~and~~
a metal film containing Cu, Ag, Sn, Ni, or Au disposed on the substrate,
wherein the substrate is attached to a semiconductor device provided in a precision electronic equipment having at least a driving portion or a sliding portion; and
an oxide film formed on a front and back surface of the heat radiating substrate.

33. (Previously Added) A heat radiating device according to claim 32, wherein the metal film consists of a plating film.

34. (Previously Added) A heat radiating device according to claim 32, wherein the metal film is configured to contact a metal body provided on a back surface of the semiconductor device.
